


VIGAS WF

Perfil tipo "I" o "H"
americano de ala ancha



DESIGNACION	DIMENSIONES (mm)					Peso (kg/m)	Área (cm ²)	Momento de Inercia (cm ⁴)		Módulo de Sección (cm ³)	
	Altura		Ala		Dist.			I _x	I _y	S _x	S _y
	h	s	b	t	r						
W6X9	150	4.32	100.1	5.5	6.0	13.41	17.3	683	91	91.1	18.2
W6X15	152	5.84	152.1	6.6	6.0	22.34	28.6	1,211	388	159.2	51.0
W6X20	157	6.60	152.9	9.3	6.0	29.79	37.9	1,723	554	218.8	72.4
W8X13	203	5.84	101.6	6.5	8.0	19.36	24.8	1,648	114	162.4	22.4
W10X12	251	4.83	100.6	5.3	8.0	17.87	22.8	2,239	91	178.6	18.0
W10X26	262	6.60	146.6	11.2	8.0	38.73	49.1	5,994	587	458.2	80.1
W12X16	305	5.59	101.3	6.7	8.0	23.83	30.4	4,287	117	281.3	23.2
W12X65	307	9.91	304.8	15.4	12.0	96.82	123.2	22,185	7,242	1443.7	475.2
W14X22	348	5.84	127.0	8.5	10.0	32.77	41.9	8,283	291	476.1	45.9
W16X26	399	6.35	139.7	8.8	10.0	38.73	49.5	12,529	399	628.3	57.1
W21X44	526	8.89	165.1	11.4	13.0	65.54	83.9	35,088	862	1334.7	104.4